L9 ANSWER 16 OF 29 CAPLUS COPYRIGHT 2003 ACS on STN

ACCESSION NUMBER:

1979:7548 CAPLUS

DOCUMENT NUMBER:

90:7548

TITLE:

Water-resistant and oil-resistant textiles

INVENTOR(S):

Kirimoto, Kazusuke

PATENT ASSIGNEE(S):

Asahi Glass Co., Ltd., Japan

SOURCE:

Jpn. Kokai Tokkyo Koho, 6 pp.

CODEN: JKXXAF

DOCUMENT TYPE:

Patent

LANGUAGE:

Japanese

FAMILY ACC. NUM. COUNT: 1

PATENT INFORMATION:

PATENT NO. KIND DATE APPLICATION NO. DATE

JP 53081799 A2 19780719 PRIORITY APPLN. INFO.:

JP 1976-157402 19761228

JP 1976-157402 19761228

AB Water- and oil-resistant cotton or polyester fabrics with improved hand were prepd. by mixing a poly(dimethylsiloxane) or Me H polysiloxane (I) with a polymer based on RZCO2CR1:CH2, where R is a C4-15 perfluoroalkyl group, Z is a C1-10 alkylene, and R1 is H or Me, and finishing the fabric with the mixt. Thus, an ***emulsion*** contg. a mixt. (A) of a 4:3:2:1 CH2:CHCO2(CH2)3(CF2)4CF(CF3)2-

CH2:CHCO2(CH2)3(CF2)6CF(CF3)2-

CH2:CHCO2(CH2)3(CF2)8CF(CF3)2-CH2:CHCO2(CH2)3(CF2)10CF(CF3)2 copolymer [

68508-80-5] 73, Et ***acrylate*** 25, and diacetone acrylamide 2 wt.% 100, an emulsifier 9, and C18H37N+Me3Cl- 1 part and I were mixed. A polyester doeskin was immersed in the resulting mixt. to 90% pickup, dried, and heated 1 min at 170.degree. to give a smooth water- and oil-resistant fabric with A mixt. content 0.04% and I content 0.02%, whereas the hand of a fabric treated with a similar compn. without I was not smooth.